

# CITIZEN

## MOVEMENT SPECIFICATIONS

CAL. 2035 BY CITIZEN WATCH CO., LTD. JAPAN

6-3/4X8 LIGNE, QUARTZ, NO(0) JEWEL

MADE IN JAPAN

### 1. BASIC SPECIFICATION

(1) CAL. NO.

CALIBRE	2025	2035	2034
Size	15.3 x 17.8mm		
Total thickness	3.15mm		
Hands	2	3	3
Battery life	3	3	1.2

(2) Time standard

Type of battery : Tuning fork type quartz crystal  
Oscillation : 32,768Hz  
Accuracy : +/- 20 s/month worn under normal circumstances

(3) Battery

Type of b. Silver oxide SR626SW or equivalent

(4) Others

Driving systems : Two-pole stepping motor  
Jewel : No jewels

(5) Additional Mechanisms

Second hand stopping at optional positic (2034,2035)

**Powercell saving reset mechanism**

**Over-loading compensation device** (2025,2035)

(6) Blanceable weight of hand

Minute hand Max. 0.3  $\mu$  N·m  
Second hand Max. 0.07  $\mu$  N·m

## 2. SEPARATED PARTS

<b>HOUR WHEEL</b>	075-193
<b>DIAL WASHER</b>	078-040
<b>SETTING STEM</b>	065-468

Remarks :

\* Setting stem

Length of movement center to stem end 20.0mm

Thread..... 0.9mm x 12.38mm

\* Measurement of time rate

The unit time of measurement must be set at "10s" or integer fold value of 10s owing to the DFC system.

And the measurement must be carried out in state of a complete watch.

\* Marking on movement

NO(0) JEWELS

CAL. NO.

MIYOTA CO., JAPAN

\* Typical clearance

Between case and movement

Battery strap - Case back : 150 - 300  $\mu$  m

Hands - glass : 300 - 450  $\mu$  m

Depending on Hand length

This specifications might be changed without prior notice.