

MOVEMENT SPECIFICATIONS
CAL. SUPER 2035 BY CITIZEN WATCH CO., LTD. JAPAN
6-3/4X8 LIGNE, QUARTZ, NO(0) JEWEL
MADE IN JAPAN

1.BASIC SPECIFICATION

(1) CAL. NO.

CALIBRE	SUPER 2035
Size	15.3 x 17.8mm
Total thickness	3.15mm
Colour	GILT
Hands	3
Battery life	4 years

(2) Time standard

Type of quartz : Tuning fork type quartz crystal
Oscillation : 32,768Hz
Accuracy : +/- **15** s/month worn under normal circumstances

(3) Battery

Type of battery : Silver oxide SR626SW 32mAH edition with **Mercury Free**

(4) Others

Driving systems : Two-pole stepping motor
Jewel : No jewels

(5) Additional Mechanisms

Second hand stopping at optional position
Powercell saving reset mechanism
Over-loading compensation device

(6) Balanceable weight of hand

Minute hand Max. 0.4 μ N·m
Second hand Max. 0.07 μ N·m

2. SEPARATED PARTS

	SUPER 2035
SETTING STEM	065-468

Remarks :

* Setting stem

Length of movement center to stem end...20.0mm

Thread..... Φ 0.9mm x 12.38mm

* Measurement of time rate

The unit time of measurement must be set at "10s", "20s", "30s"
(not "15s", "25")

And the measurement must be carried out in state of a complete watch.

* Marking on movement

NO(0) JEWELS
SUPER 2035
MIYOTA CO.
JAPAN MADE

* Typical clearance

Between case and movement
Battery strap - Case back : 150 - 300 μ m
Hands - glass : 300 - 450 μ m
Depending on Hand length

This specifications might be changed without prior notice.